

FOLD SERIES MAGNETIC TRACK LIGHT

GENERAL SPECIFICATION

The fold series can be used as a spotlight or a wall washer. The elegant design comes with either an antiglare spotlight lens which is available in several beam angles, or a soft diffused lens. The Fold series also features a adjustable head with 90° range of motion, and mounts on our 24V magnetic track system.










Beam angle: 12/34/48° CCT: 2700K/3000K/4000K

CRI: RA90

DIM: Triac,0/1-10V, Installation: Magnetic Environment: Indoor

DIMENSION



Ordering Information

Example: FOLD04-3090-24V-DL-MTM-BK

Series	Watts	_CCT&CRI	_ Voltage	Lens	Installation	- Finish
FOLD	04 - 4W	- 2790 - 2700K 90Ra	- 24V -24Vdc ¹	12 - 12 degree	MTM - Magnetic	- BK -Black ²
	08 - 08W	3090 - 3000K 90Ra		34 - 34 degree	Track Mount	Optional
	16 - 16W	4090 - 4000K 90Ra		48 - 48 degree		WH -White ²
				DL - Diffused Lens		· · · · · · · · · · · · · · · · · · ·

Notice:

- 1. The fixture is used for 24V magnectic track system.
- 2. Standard Finish is black. Custom colors might be available for an additional fee. Please check with Customer Service for more information.





4W with Spot Lens



8W with Spot Lens



16W with Spot Lens



4W with Diffused Lens



8W with Diffused Lens




16W with Diffused Lens

PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.


Diffuso



h(m)	E(Ix)	Φ(m)
1	3693	Ф0.23
2	923	Ф0.47
3	410	Ф0.71
4	230	Ф0.94
5	147	Ф1.18



h(m)	E(lx)	Φ(m)
1	1238	Ф0.61
2	309	Ф1.22
3	137	Ф1.83
4	77	Ф2.44
5	49	Ф3.05



h(m)	E(I	x) Φ(m)
1	77	'8 Ф0.91
2	19	Ф1.82
3	86	6 Ф2.73
4	48	В Ф3.64
5	3	1 Ф4.55

Dilluse	
500	300

h(m)	E(Ix)	Ф(т)
1	105.5	Ф2.60
2	26.3	Ф5.20
3	11.7	Ф7.80
4	6.5	Ф10.40
5	4.2	Ф13.00

PERFORMANCE DATA

Lumen values are estimated with LED data sheet.

Watts	Lumen Output	CRI	Lens	CCT	LPW
4	380	90	12/34/48°	3000K	95
8	790	90	12/34/48°	3000K	98
16	1550	90	12/34/48°	3000K	97
4	280	90	Diffused	3000K	70
8	500	90	Diffused	3000K	63
16	980	90	Diffused	3000K	61

Warranty

Five year limited warranty.

^{*} Specifications subject to change without notice.