





THOE LED WALL LIGHT







PRODUCT DESCRIPTION

The Thoe wall light is designed in an architecture minimalist cuboid shape. It combines die-cast aluminium structure and glass lens in one integral shape. Direct and indirect distributions. Suitable for both indoor and outdoor wall light applications.

FEATURE

- · Die-cast aluminum housing
- · AC LED, without driver
- · Clear glass lens
- · Direct and indirect light
- · IP65 for wet locations

ELECTRICAL SYSTEM

Input voltage: 120V

• 50/60Hz

Power Factor: >0.97

Working Temperature: -4-104°F (-20-40°C)

PERFORMANCE

CRI

80

CCT

3000K

Dimming

Non dimming

Projected Lifetime

L70 -100,000 Hours

Working Temperature

-4-104°F (-20-40°C)


Certifications

- cETLus listed
- · IP65 for wet locations
- · RoHs compliant

SPECIFICATION


Short

Net Weight: 2.5lbs (1.13kg)



Long

Net Weight: 4.47lbs (2.03kg)



Ordering Information

Example: TSID18304-BK

Name	Distribution	Watts	CCT	Voltage	Control	Finish
TS-Thoe Short	D - Direct	09 - 9W	30 - 3000K	4 -120	Blank - None	BK - Black
	ID- Indirect and Direct	18 - 18W				
TL-Thoe Long	D - Direct	18 - 18W	30 - 3000K	4 -120	Blank - None	BK - Black
	ID- Indirect and Direct	36 - 36W				


Notice:

^{*} Black finish is standard. Other finish color is available at an additional charge.



PHOTOMETRY

All published luminaire photo metric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.



Direct and Indirect

PERFORMANCE DATA LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Watts	Lumen Output	AC Input 120V	CCT	CRI
9	520	0.07A	3000K	80
18	1060	0.15A	3000K	80
36	2160	0.30A	3000K	80

BUG Rating

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory

Model	BUG Rating		
TSD09304	B0-U1-G0		
TSID18304	B0-U4-G0		
TLD18304	B1-U2-G1		
TLID36304	B1-U5-G0		



Direct Light



Direct and Indirect Light

Warranty

Three year limited warranty.

Specifications subject to change without notice.