




IMAGE MAY VARY FROM ACTUAL PRODUCT

## LED FULL CUT-OFF WALL PACK



### PRODUCT DESCRIPTION

LED Wall Packs are designed and engineered as maintenance free, energy-efficient alternatives to traditional fluorescent, high & low pressure sodium, metal halide, induction, and other types of light sources.

### CONTROL

**Photo control:** Voltage-specific photocontrols power the fixture when light levels reach 20 lux or below, and turn it off at 30 lux or higher.

Operating temperature is 30°F-120°F. Photocell mounted externally.

**Motion/Daylight sensor:** 0-10V microwave-based motion sensor with integral photocontrol, featuring high/low motion detection. Field adjustable for 100% light output in the high with 10, 20, 30, 50 or 0% on the low side. Detection area, hold time, daylight threshold, and dimming level all have DIP switches.

Operating temperature is -31-158°F. At its maximum mounting height of 32 feet, the sensor can detect motion up to 30 feet away. Sensor mounted internally behind glass.

#### Ordering Information

**Example: ABWP40LED50DS-MS**

ABOVE ALL	Wall Pack	Watts	Source type	CCT	Distribution	Controls
AB/ ABB*	WP	20-20 Watts	LED	30 - 3000K	DS - Full Cut off	MSW-Microwave Motion Sensor
		30-30 Watts		40 - 4000K		PC12-Photo Control 120V
		40-38 Watts		50 - 5000K		PC27-Photo Control 277V
		60-52 Watts				EBU-Emergency Backup
						Leave blank for no controls

Notice:


- Standard Finish as Traditional Bronze.
- DLC Premium only with 5000K at present.
- Special Order as other finish color - Ask Customer Service for Details.

Only 20W use with AB\*

30W, 40W, 60W use with ABB

**Add:** 1501 Industrial Way N, Toms River, NJ 08755 **Phone:** 866-222-8866

**Web:** www.AboveAllLighting.com ©2016 ABOVE ALL Lighting, Inc. All rights reserved



## PERFORMANCE DATA

### LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

### Lumen Ambient Temperature (LAT) Multipliers

Use these factors to determine relative lumen output for average ambient temperature from -40-104°F (-40-40°C)

Watts	Lumen Output	AC Input 120V	Measured Watts	CRI	Dist. Type	LPW
20W	2100	0.19A	19W	>70	Full Cut Off	<b>92</b>
30W	3100	0.28A	30W	>70	Full Cut Off	<b>111</b>
40W	3700	0.37A	38W	>70	Full Cut Off	<b>110</b>
60W	5600	0.55A	52W	>70	Full Cut Off	<b>113</b>

Ambient		Multiplier
Celsius	Fahrenheit	
0	32	1.02
10	50	1.01
20	68	1.00
25	77	1.00
30	86	1.00
40	104	0.99


### Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the LED Wall Pack in a 77°F ambient, (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).


Operating Hours	0	25,000	50,000	100,000	<b>250,000</b>
Lumen Maintenance Factor	1.0	0.98(L98)	0.96(L96)	0.92(L92)	<b>0.70(L70)</b>

### Photometry


All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.




**20W**



**30W**



**40W**



**60W**

## PRODUCT SPECIFICATIONS

### CONSTRUCTION & MATERIALS

- Housing is all aluminum construction
- Terminal block for power input suitable for 2 - 10 AWG wire
- Luminaire sides are rugged die cast aluminum with integral, weathertight LED driver compartments and high performance heat sinks
- Surface-mount directly to a vertical or horizontal surface with direct included mount bracket

System Wattage	Max THD (%)	Power Factor	Power Efficiency	Replaces/ Equiv.(MH)
20W	20	>0.9	90%	125W
30W	20	>0.9	90%	150W
40W	20	>0.9	90%	175W
60W	20	>0.9	90%	250W

Ref#:10150-10118

### ELECTRICAL SYSTEM

- Input Voltage: 120-277V/120V/277V
- 50/60Hz
- Class II driver
- Minimum Ambient -40°C
- Total Harmonic Distortion: < 20% at full load

### CERTIFICATIONS AND QUALIFICATIONS

- cETLus Listed
- Suitable for wet location
- DLC qualified. Please refer to <http://www.designlights.org/QPL> for most current information
- RoHS compliant
- Complies with 2013 California Title 24 building and electrical codes as a residential outdoor lighting fixture and as a commercial outdoor non-pole-mounted fixture ≤ 30 Watts

### Warranty

Five year limited warranty. Full warranty terms located at [www.abovealllighting.com/warrantystatements](http://www.abovealllighting.com/warrantystatements)

**Note:** Specifications subject to change without notice.