



PL Direct Wire Tube



Ref#: 10241-10504

PRODUCT DESCRIPTION

LED PL Replacement Lamps are the ideal energy saving choices when upgrading traditional CFL PL. Universal voltage 120V-277Vac. Beam angle is 280°.

Ordering Information

Example: PG15271G

PL Retrofit Lamp	Watts	CCT	AC Direct Wire	Base
PG	08 - 8W	27 - 2700K	1 - 120-277V	G - GX24q
	11 - 11W	30 - 3000K		
	15 - 15W	40 - 4000K		
		50 - 5000K		

Notice:

1. Standard Finish as White.
2. Special Order as other finish color - Ask Customer Service for Details.

SPECIFICATIONS

	8W	11W	15W
Voltage	120-277V	120-277V	120-277V
Power	8W	11W	15W
Color Temperature	2700K/3000K/4000K/5000K	2700K/3000K/4000K/5000K	2700K/3000K/4000K/5000K
Power Factor	>0.9	>0.9	>0.9
Lumen Output	770lm	1000lm	1400lm
LPW	87lm/W	87lm/W	97lm/W
CRI	>80	>80	>80
Beam Angle	280°	280°	280°
Base Type	GX24q	GX24q	GX24q
Life Time	15000H	15000H	15000H
Operating Temperature	-4°F - 104°F	-4°F - 104°F	-4°F - 104°F
Operation Environment	Indoor	Indoor	Indoor
Dimension(L-W-H)	1.57" x1.57" x 5.49"	1.57" x1.57" x 5.49"	1.57" x1.57" x 6.49"
Weig (lbs)	0.39lb	0.39lb	0.39lb
Standard	UL,FCC,RoHs	UL,FCC,RoHs	UL,FCC,RoHs
Replace Wattage	13W CFL	18W CFL	26W CFL