

LED T8 Glass Bypass Tube DLC 4.1

Ref#: 11636-10416



PRODUCT DESCRIPTION

LED T8 Linear Replacement Lamps are the ideal energy saving choices when upgrading traditional linear T8. Universal voltage 120V-277Vac. For use with non-shunted sockets only.

Ordering Information

Example: T811401-FW12-GL

Size	Watts	CCT	AC Direct Wire	Lens Type	Length	Glass Type
T8	11 -11.5 W 14 -14.5 W	40 - 4000K 50 - 5000K	1-120-277V	FW- Frost White	12 - 4 FT	GL - Glass

Notice:

1. Standard Finish as Frost White.
2. Special Order as other finish color - Ask Customer Service for Details.

SPECIFICATIONS

Voltage	120-277Vac	120-277Vac
Power	11.5W	14.5W
Color Temperature	4000K/5000K	4000K/5000K
Power Factor	0.9	0.9
Lumen Output	1800lm	2200lm
LPW	145	140
CRI	>80	>80
Beam Angle	160°	160°
Harmonic Distortion	15%	15%
Base Type	G13 (Single-Ended)	G13 (Single-Ended)
Life Time	50000H	50000H
Operating Temperature	-4°F~113°F	-4°F~113°F
Operation Environment	Indoor	Indoor
Dimension(L-W-H)	Φ1" * 47.76"	Φ1" * 47.76"
Weig (lbs)	0.68lb	0.68lb
Standard	UL/DLC/FCC/RoHS	UL/DLC/FCC/RoHS
Target Replacement lamps	4ft: F32T8 F30T8 F28T8 F25T8	4ft: F32T8 F30T8 F28T8 F25T8