

SUITABLE FOR MODEL



SAFETY INSTRUCTION



READ CAREFULLY BEFORE INSTALLING FIXTURE. PLEASE KEEP THIS MANUAL FOR FUTURE USE.

Fixtures must be wired in accordance with the National Electrical Code and all applicable local codes. Proper grounding is required for safety.

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

MAKE CERTAIN POWER IS OFF BEFORE INSTALLING OR MAINTAINING FIXTURE.

CHECK THAT VOLTAGE IS COMPATIBLE WITH FIXTURE DRIVER. USE APPROVED CONNECTORS FOR ALL ELECTRICAL CONNECTIONS.

MAINTENANCE CAUTION



1. Review the wire connection before beginning, and make sure fixture is grounded properly.
2. For lighting controls, follow control instructions carefully.
3. Turn power off and wait for fixture to cool before performing maintenance.
4. Maintenance must be done by professionals.


WIRE CONNECTION

Universal Voltage permits operation at 120VAC thru 277VAC or 347VAC, 50 or 60 Hz.

Make the following Electrical Connection:

- a). Connect the voltage supply line to ACL in Black.
- b). Connect the voltage supply Neutral to ACN in White.
- c). Connect Green ground lead to the supply ground lead.

120-277V/347V



INSTALLATION


WARNING

Risk of injury or damage. Make certain power is OFF before installing or maintaining fixture.

ACCESSORY PACK



WIRE NUT x 3



SCREW & WASHER x 4

INSTALLATION STEPS

1. Drill proper mounting holes on the wall according to the Drill Pattern. Fasten the Mounting Bracket on the wall with screw (by others).
2. Make wire connection according to wiring diagram.
3. Insert Screw B (2) into the Slots (2) at the side of Mounting bracket to hook the fixture on the Mounting Bracket.
4. Fasten Fixture to the Mounting Bracket with Screw A and Washer (4). The end with Up-Arrow label must be up. All wires and terminals need to be pushed into J-Box and no wires get pinched.
5. Seal around the top and side perimeter between the fixture and the wall surface with weather resistant caulking (by others). Pay attention the space at bottom should be left un-caulked to prevent moisture build-up.

Drill Pattern

