

SUITABLE FOR MODEL



IMAGE MAY VARY FROM ACTUAL PRODUCT

SAFETY INSTRUCTION

READ CAREFULLY BEFORE INSTALLING FIXTURE. PLEASE KEEP THIS MANUAL FOR FUTURE USING.

Fixtures must be wired in accordance with the National Electrical Code and all applicable local codes. Proper grounding is required for safety.

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.



MAKE CERTAIN POWER OFF BEFORE INSTALLING OR MAINTAINING FIXTURE.

CHECK THAT VOLTAGE IS COMPATIBLE WITH FIXTURE DRIVER, USE APPROVED CONNECTORS FOR ALL ELECTRICAL CONNECTIONS.

MAINTENANCE CAUTION

1. Review the diagrams before beginning, and make sure fixture is grounded properly.
2. For lighting controls, using functioning correctly.
3. Turn power off and wait for fixture cooling to operate.
4. Maintenance must be done by professionals.

WIRE CONNECTION



WARNING

WARNING-RISK OF FIRE OR ELECTRIC SHOCK. Installaion requires knowledge of the lighting luminaires electrical systems. If not qualified, do not attempt installation and contact a qualified electrician.

Voltage input: 120-277V 50/60 Hz

Operating temp: -4°F to 104°F

**Consult with dimmer control manufacturer's wiring instructions

INSTALLATION


RECESSED MOUNT

1. Please check the fitting bag with components list.
2. Comparing with the specification as follows, judging if the ceiling is meeting the installation requirement for recessed installation.


SPEC	Size/mm	External size of Tchannel/mm	Internal size of Tchannel/mm	N. W. / Kg
1x4	300x1(L)*1210x1(W)	280x1(L)*1190x1(W)	303x1(L)*1213x1(W)	4
2x2	600x1(L)*600x1(W)	580x1(L)*580x1(W)	603x1(L)*603x1(W)	4
2x4	600x1(L)*1210x1(W)	580x1(L)*1190x1(W)	603x1(L)*1213x1(W)	7.5

! Please confirm the dimensions of the ceiling channel and the lamp is matching.
! Please confirm load-bearing is enough to support the lamp.


3. Take the ceiling panel down.




4. Lift up four(four for 2X2,six for 1X4 and 2X4) mounting clips on the sides of the luminaire.
You can do it by hand(Do wear work gloves) or use pliers.



5. Insert luminaire into T-bar ceiling grid. Secure safety cable to connection hole as needed to meet local seismic requirements. Safety cable and method of attachment to the building provided by contractor according to local building codes.



6. Please check if the lamp have been fixed in the ceiling channel.



WARRANTY

LIMITED FIVE-YEAR WARRANTY. Should this product fail to perform satisfactorily due to a defect or poor workmanship within five years from the date of purchase, return it to the place of purchase and it will be replaced, free of charge. Incidental or consequential damages are excluded from the warranty.