

LED T8 PC Direct Wire Tube



Ref#: 10135-10118

PRODUCT DESCRIPTION

LED T8 Linear Replacement Lamps are the ideal energy saving choices when upgrading traditional linear T8. Universal voltage 120V-277Vac. For use with non-shunted sockets only.

Ordering Information

Example: T810xx1-FW06

Size	Watts	CCT	AC Direct Wire	Lens Type	Length
T8	10 - 10 W	41 - 4100K	1-120-277V	FW- Frost	06 - 2 FT
	18 - 18 W	50 - 5000K		White	12 - 4 FT
	22 - 22 W				

Notice:

1. Standard Finish as Frost White.
2. Special Order as other finish color - Ask Customer Service for Details.

SPECIFICATIONS

Model No.	T810xx1-FW06	T818xx1-FW12	T822xx1-FW12
Voltage	120-277Vac	120-277Vac	120-277Vac
Power	10W	18W	22W
Color Temperature	4100K/5000K	4100K/5000K	4100K/5000K
Power Factor	0.9	0.9	0.9
Lumen Output	1000lm	1900lm	2350lm
LPW	90	94	107
CRI	>80	>80	>80
Beam Angle	160°	160°	160°
Harmonic Distortion	15%	15%	15%
Base Type	G13 (Single-Ended)	G13 (Single-Ended)	G13 (Single-Ended)
Life Time	50000H	50000H	50000H
Operating Temperature	-4°F~113°F	-4°F~113°F	-4°F~113°F
Operation Environment	Indoor	Indoor	Indoor
Dimension(L-W-H)	Φ1" * 23.78"	Φ1" * 47.76"	Φ1" * 47.76"
Weig (lbs)	0.68lb	0.68lb	0.68lb
Standard	UL/DLC/FCC/RoHS	UL/DLC/FCC/RoHS	UL/DLC/FCC/RoHS
Target Replacement lamps	F17T8 (2ft)	4ft: F32T8 F30T8 F28T8 F25T8	4ft: F32T8 F30T8 F28T8 F25T8

Add: 1501 Industrial Way N, Toms River, NJ 08755 **Phone:** 866-222-8866

Web: www.AboveAllLighting.com ©2016 ABOVE ALL Lighting, Inc. All rights reserved