



IMAGE MAY VARY FROM ACTUAL PRODUCT

# LED Security Light




## PRODUCT DESCRIPTION

LED Security Light is the ideal for security entrance, stairways, and storage area. Integral Photocell is preinstalled for more efficient operation and energy savings. Available in 120V only.

## SPECIFICATION

Length: 10.9"  
 Width: 6.8"  
 Height: 5.2"  
 Max. Weight: 3.39 lbs



## Ordering Information

**Example: ABBSEC14504**

ABOVE ALL	Security Light	Watts	CCT	Voltage
ABB	SEC	14 - 14 Watts	30 - 3000K 40 - 4000K 50 - 5000K	4 - 120V

Notice:

1. Standard Finish as Traditional Bronze.
2. DLC Premium only with 5000K at present.
3. Special Order as other finish color - Ask Customer Service for Details.

## PERFORMANCE DATA

### LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

### Lumen Ambient Temperature (LAT) Multipliers

Use these factors to determine relative lumen output for average ambient temperature from -40-104°F (-40-40°C)

Watts	Lumen Output	AC Input 120V	Measured Watts	CRI	Dist. Type	LPW
14W	1201	0.13A	14W	>80	N/A	80

Ambient		Multiplier
Celsius	Fahrenheit	
0	32	1.02
10	50	1.01
20	68	1.00
25	77	1.00
30	86	1.00
40	104	0.99


### Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the LED Security Light in a 77°F ambient, (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

Operating Hours	0	4,000	7,000	30,000	175,000
Lumen Maintenance Factor	1.0	0.98(L98)	0.96(L96)	0.92(L92)	0.70(L70)

### Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.



## PRODUCT SPECIFICATIONS

### CONSTRUCTION & MATERIALS

- Housing is all aluminum construction
- Terminal block for power input suitable for 2 - 10 AWG wire
- Luminaire sides are rugged die cast aluminum with integral, weathertight LED driver compartments and high performance heat sinks

System Wattage	Max THD (%)	Power Factor	Power Efficiency	Replaces/ Equiv.(MH)
14W	20	>0.9	90%	70W

Ref#: 10488-10118

### ELECTRICAL SYSTEM

- Input Voltage: 120V
- 50/60Hz
- Class II driver
- Minimum Ambient -40°C
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load

### CERTIFICATIONS AND QUALIFICATIONS

- cETLus Listed
- Suitable for wet location
- IP65 rated
- DLC qualified. Please refer to <http://www.designlights.org/QPL> for most current information
- RoHS compliant

**BUG RATING**

Model	BUG Rating
ABBSEC14504	B0-U3-G2

**Warranty**

Five year limited warranty. Full warranty terms located at [www.aboveallLighting.com/warrantystatements](http://www.aboveallLighting.com/warrantystatements)

**Note:** Specifications subject to change without notice.