

LS Parking Garage Light



IMAGE MAY VARY FROM ACTUAL PRODUCT





PRODUCT DESCRIPTION

The LS series parking garage lights are the high-performance solution for the most demanding applications within a patented air cooling design. With an expected service life of 70,000 hours and an easy-install design, it provides an affordable initial cost and low total cost of ownership. With high lumen packages and precision refractive optics, the LS series can meet superior illumination performance requirements.

SPECIFICATION

Dimension(L-W-H): 12"-12"-3.7"
 Max. Weight: 13.5 lbs



Ordering Information

Example: LSPKG35501-MS

LS Series Parking Garage Lights	Watts	CCT	Voltage	Controls
LSPKG	35 - 36 Watts	30 - 3000K	1 - 120-277V	MS - Multi-level Motion Sensor
	65 - 70 Watts	40 - 4000K	6 - 347/480V	
		50 - 5000K		

Notice:

- Standard Finish as White and Traditional Bronze.
- Special Order as other finish color - Ask Customer Service for Details

PRODUCT FEATURE

1. Patented Air Cooling Design
2. IP65 Rated Enclosure
3. Surface or Pendant Mounting
4. Superior Low-glare Illumination
5. Programmable Multi-level Motion Sensor
6. Impact Resistant Prismatic Lens
7. Performance up to 136 LPW
8. 5 Year Warranty Based on 40 °C



Programmable multi-level dimming motion sensor featured



Prism design, no glare




Patented air cooling design

MOUNTING OPTION

1. Pendant

2. Surface



PERFORMANCE DATA

LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Watts	Lumen Output	AC Input 120V	Measured Watts	CRI	Dist. Type	LPW
35W	4528	0.32A	35W	>80	Type V	130
65W	9172	0.60A	68W	>80		136

Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the LED LS parking garage light in a 77°F ambient, (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

Lumen Ambient Temperature (LAT) Multipliers


Use these factors to determine relative lumen output for average ambient temperature from -40-104°F (-40-40°C)

Ambient		Multiplier
Celsius	Fahrenheit	
0	32	1.02
10	50	1.01
20	68	1.00
25	77	1.00
30	86	1.00
40	104	0.99

Operating Hours	0	4,000	7,000	30,000	175,000
	Lumen Maintenance Factor	1.0	0.98(L98)	0.96(L96)	0.92(L92)

Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.



PRODUCT SPECIFICATIONS

ELECTRICAL SYSTEM

- Input Voltage: 120-277VAC, 347/480V
- 50/60Hz
- Operating temperature range: -40°C-40°C
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load

System Wattage	Max THD (%)	Power Factor	Power Efficiency	Replaces/ Equiv.(MH)
35W	20	>0.9	90%	175W
68W	20	>0.9	90%	320W

Ref#: 10325-20117

CERTIFICATIONS AND QUALIFICATIONS

- cETLus Listed
- IP65 rated
- DLC Premium listed
- RoHS compliant

LS PARKING GARAGE LIGHT RATED LIFE

Ambient Temp in	73°F	104°F	113°F	122°F
36W Rated Life	78,000H	76,000H	57,000H	40,000H
70W Rated Life	78,000H	72,000H	66,000H	61,000H

BUG RATING

Model	BUG Rating
LSPKG35501	B2-U2-G2
LSPKG65501	B3-U3-G3

Warranty

Five year limited warranty. Full warranty terms located at www.aboveallighting.com/warrantystatements

Note: Specifications subject to change without notice.