

Project Name	
Product Code	
SKU No	
Лето	
Data	



3000K	4000K	5000K		
CCT SELECTABLE				
WATTAGE SELECTABLE				

PRODUCT DESCRIPTION

The TAAP series canopy light comes in raditional construction design with LED solution. Die-cast aluminium housing. UV protected polycarbonate lens.Painting finish with high durability and long-lasting color It can be used in many canopy and parking garage applications.

FEATURES

- Die-cast aluminum housing
- 3000K, 4000K and 5000K selectable
- Wattage selectable


ELECTRICAL SYSTEM

- Input voltage: 120-277V,50/60Hz
- Power Factor: >0.9
- Total Harmonic Distortion: <20% at full load
- Working Temperature: -40~40°C (-40~104°F)

SPECIFICATION

L(Length) x W(Width)x H(Height)

243mm[9 1/2"] x 243mm[9 1/2"] x85mm[33/4"]



866-222-8866 info@abovealllighting.com www.AboveAllLighting.com

TAAP LED CANOPY



PERFORMANCE

CRI 70

ССТ

3000K × 4000K × 5000K

Dimming

0-10V Dimming Standard

Projected Lifetime

L70 -50,000 Hours

Working Temperature -40-104°F (-40-40°C)

Certifications

- cETLus
- Suitable for wet locations
- RoHS compliant
- · Sale in US only



Ordering Information

Example: CANT-40SP-SW1

Name	- Watts	- CCT	Voltage	- Control-	- Finsh
CANT	40SP - Selectable Power 24W/32W/40W ¹	SW - Selectable White 3000K/4000K/5000K ²	1 -120-277V	- Blank - None	- Blank - Bronze
	75SP - Selectable Power 45W/60W/75W ¹				

Notice:

- 1. 75W and 120W are default setting, If need other wattage, please contact Customer Service in advance to change the setting in factory or change the setting in the field
- 2. 4000K is default setting. If need other CCT please contact Customer Service in advance to change the setting in factory or change the setting in the field.
- * Standard Finish is Bronze. Custom colors might be available for an additional fee. Please check with Customer Service for more information.

PERFORMANCE DATA

LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Power(W)	24 W	32W	40W	45W	60W	75W
Lumen	3120lm	4160lm	5200lm	5850lm	7800lm	9750lm
ССТ			5000K			
Efficacy	cy 130lm/W					
CRI			70			

Warranty

Five years limited warranty is standard. Ten years limited warranty can be option.

Note:

Specifications subject to change without notice.