



VERTICAL MINI LED STEP LIGHT







PRODUCT DESCRIPTION

3W LED step/wall lights are available in a vertical configuration for mounting into a Junction box. For poured concrete and masonry installations. For indoor and protected outdoor use.

Input voltage: 120V


50/60Hz


Power Factor: >0.87

Working Temperature: -13-95°F (-25-35°C)

ELECTRICAL SYSTEM

SPECIFICATION





PERFORMANCE

CRI

80

CCT

3000K

Dimming

Non dimming

Projected Lifetime

L70 -100,000 Hours

Working Temperature

-13-95°F (-25-35°C)

Certifications

- ETL listed
- · Suitable for wet locations
- RoHs compliant

Ordering Information

Example: VMSL03304-BK

Model	Watts	CCT	Voltage	Control	Finish
VMSL	03 - 03W	30 - 3000K	4 -120	Blank - None	BK - Black


Notice:

- Minimum order required, please contact customer service for additional information.
- * Black finish is standard. Custom color is available for a premium setup fee. Consult customer service for additional information.



PHOTOMETRY

All published luminaire photo metric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.



PERFORMANCE DATA LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Watts	Lumen Output	AC Input 120V	ССТ	CRI
3	80	0.03A	3000K	80

BUG Rating

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating		
VMSL03304-BK	B0-U1-G0		

Warranty

Two year limited warranty. Full warranty terms located at www.aboveallLighting.com/warrantystatements

Note:

Specifications subject to change without notice.