ARBOR LED BOLLARD





Optional Pole Finishing



Light wood texture



Deep wood texture







RoH



The Arbor LED Bollard features attractively shielded light distribution, with a fully shielded light source that effectively minimizes upward light spill for enhanced safety and passerby comfort. Constructed with superior UV-resistant powder coating, a high-quality die-cast aluminum body, tempered safety glass lens, molded silicone gasket, and stainless steel screws, it delivers durability and precision. A distinctive wood texture finish is also available. This bollard is an excellent choice for walkways, entrances, promenades, plazas, courtyards, driveways, bridges, and landscaped areas.

TECHNICAL DATA

Wattage	10W
CRI	80
ССТ	3000K, 4000K
	3000K-DarkSky Approved
Dimming	Non-Dimming
Input Voltage	120-277V, 50/60Hz
Operating Temp.	-22°F to 104°F(-30°C to 40°C)
Certifications	cETL listed
	Suitable for wet location
	RoHS compliant
	DarkSky Approved for CCT of
	3000K and below
Power Factor	>0.9 at 120 Vac
Harmonic Distortion	<20% at full load
Projected Lifetime	L70 - 100,000 Hours
IP Rating	IP65

FEATURES

- Optimized Visual Comfort: Fully shielded light source.
- Versatile Application: Ideal for a wide range of exterior spaces.
- Premium Construction: UV powder-coated die-cast aluminum body. Molded silicone gasket & stainless steel screws.

ARBOR LED BOLLARD



SPECIFICATION

Dimension

Side View



Base Plate

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CRI	ССТ
10W	490LM	0.08A	80	3000K



ORDERING INFORMATION

Standard Model

EXAMPLE: ARBD32H-10401-BK

ARBD Series	Height	Wattage	сст	Voltage	Control	Finish
ARBD Arbor Bollard	32H 31.5" Height	10 10W	30 3000K	1 120-277V	BLANK On/Off	BK Black
			40 4000K			Wood Texture Optional ¹ Additional fees applied.

NOTE:

1. The standard color is black finish; Wood texture finish and other optional finish colors are available at an additional charge. Please contact Customer Service for details.

DarkSky-Approved Model

EXAMPLE: ARBD32H-10301-BK

ARBD Series	Height	Wattage	ССТ	Voltage	Control	Finish
ARBD Arbor Bollard	32H 31.5" Height	10 10W	30 3000K	1 120-277V	BLANK On/Off	BK Black
						Wood Texture Optional ¹ Additional fees applied.

NOTE:

1. The standard color is black finish; Wood texture finish and other optional finish colors are available at an additional charge. Please contact Customer Service for details.

ARBOR LED BOLLARD



WOOD TEXTURE OPTIONS



LWTC-1/2-TP

Pole finish 1/2 light wood texture on the top, and 1/2 black on the bottom. **LWTC-2/3-TP** Pole finish 2/3 light wood texture on the top, and 1/3 black on the bottom.



DWTC-1/2-TP Pole finish 1/2 deep wood texture on the top, and 1/2 black on the bottom. DWTC-2/3-TP Pole finish 2/3 deep wood texture on the top, and 1/3 black on the bottom.

75 black off the bottom. Dia

Notes: For alternative finish/paint ratios, please contact Customer Service.

ACCESSORIES (ORDERED SEPARATELY)



ABMK-ARBD

Anchor Bolts Mounting Kits.

BUG RATING TABLE

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating
ARBD32H_10301_BK	B0-U0-G0
ARBDXXH_10301_BK	B0-U0-G0

WARRANTY

5 years limited warranty. Specifications subject to change without notice.