



**DARKSKY  
APPROVED**  
Reduces Light pollution  
Certified by DarkSky.org

The Pillar Square LED Bollard features a UV powder-coated, die-cast high-quality aluminum body with a molded silicone gasket and stainless steel screws. It offers selectable wattage and CCT. This bollard is an excellent choice for entrances, walkways, driveways, promenades, courtyards, bridges, plazas, and landscaped areas.

## TECHNICAL DATA

Wattage	Selectable 10W/15W/20W
CRI	80
CCT	Selectable 3000K/4000K/5000K
Driver	Non-Dimming is standard 0-10V Dimming is optional
Input Voltage	120-277V
Operating Temp.	-86°F to 104°F (-30°C to 40°C )
Certifications	cETL listed Suitable for wet location RoHS compliant DarkSky Approved for CCT of 3000K and below
Power Factor	>0.9 at full load
Harmonic Distortion	<20% at full load
Projected Lifetime	L70 - 100,000 Hours
IP Rating	IP65


## FEATURES

- **Adjustable & Customizable:** Selectable wattage and selectable CCT.
- **Premium Construction:** UV powder-coated die-cast aluminum body. Molded silicone gasket & stainless steel screws.


SPECIFICATION

Dimension


Axonometric View




Side View



Top View



ANCHOR BOLTS



PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CRI	CCT
10W	1100 lm	0.08A	80	3000K
15W	1500 lm	0.13A	80	3000K
20W	2000 lm	0.17A	80	3000K

## ORDERING INFORMATION

## Standard Model

EXAMPLE: PSBD40H-SP-SW1-BK

PSBD						
Series	Height	Wattage	CCT	Voltage	Control	Finish
PSBD Pillar Square Bollard	40H 39.4" Height	SP <sup>1</sup> Selectable <sup>1</sup> 10W 15W 20W	SW <sup>2</sup> Selectable <sup>2</sup> 3000K 4000K 5000K	1 120-277V	BLANK On/Off	BK Black  Optional Finish Colors <sup>3</sup> Custom Colors <sup>3</sup> Additional fees applied.

## NOTE:

- 20W is the default setting.
- 3000K is the default setting.
- The standard color is black finish. Custom colors are available for an additional charge.

## ORDERING INFORMATION

## DarkSky-Approved Model


EXAMPLE: PSBD40H-20-301-BK-D

PSBD						
Series	Height	Wattage	CCT	Voltage	Finish	Options
PSBD Pillar Square Bollard	40H 39.4" Height	20 20W	30 3000K	1 120-277V	BK Black  Optional Finish Colors <sup>1</sup> Custom Colors <sup>1</sup> Additional fees applied.	D 0-10V dimming

## NOTE:

- The standard color is black finish. Custom colors are available for an additional charge.

ACCESSORIES (ORDERED SEPARATELY)



**ABMK-PSBD**  
Anchor Bolts Mounting Kits.

BUG RATING TABLE

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating
PSBD 10W 3000K	B1-U0-G0
PSBD 10W 4000K	B1-U0-G0
PSBD 10W 5000K	B1-U0-G0
PSBD 15W 3000K	B1-U0-G0
PSBD 15W 4000K	B1-U0-G0
PSBD 15W 5000K	B1-U0-G0
PSBD 20W 3000K	B1-U0-G0
PSBD 20W 4000K	B1-U0-G0
PSBD 20W 5000K	B1-U0-G0

WARRANTY

5 years limited warranty.  
Specifications subject to change without notice.